



UL2464系列電纜

鋁箔各隔+鋁箔銅網總隔

產品說明 Product manual

標準:UL2464

對絞集合每對鋁箔麥拉個別遮蔽加地線再鋁箔麥拉鍍錫銅網整體隔離加地線

規格:18AWG-24AWG

芯數:2C-100C

導體:鍍錫銅

絕緣:SR-PVC

外被:PVC

耐溫:80°C

標準電壓:300V

線號	線數/線徑	對數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Pair	MM	MM	MM	Product
24	7/0.20	2	0.23	1.10	5.5	
24	7/0.20	3	0.23	1.10	6.5	
24	7/0.20	4	0.23	1.10	7.0	
24	7/0.20	5	0.23	1.10	8.0	
24	7/0.20	6	0.23	1.10	9.2	
24	7/0.20	7	0.23	1.10	9.6	
24	7/0.20	8	0.23	1.10	9.9	
24	7/0.20	9	0.23	1.10	10.4	
24	7/0.20	10	0.23	1.10	11.0	
24	7/0.20	12	0.23	1.10	12.1	
24	7/0.20	14	0.23	1.10	12.7	
24	7/0.20	16	0.23	1.10	13.4	
24	7/0.20	18	0.23	1.10	13.9	
24	7/0.20	20	0.23	1.10	14.5	
24	7/0.20	25	0.23	1.10	16.6	
24	7/0.20	30	0.23	1.10	17.5	
24	7/0.20	40	0.23	1.10	19.0	
24	7/0.20	50	0.23	1.10	20.8	

線號	線數/線徑	對數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Pair	MM	MM	MM	Product
22	17/0.16	2	0.23	1.30	6.0	
22	17/0.16	3	0.23	1.30	7.0	
22	17/0.16	4	0.23	1.30	7.5	
22	17/0.16	5	0.23	1.30	8.7	
22	17/0.16	6	0.23	1.30	10.0	
22	17/0.16	7	0.23	1.30	10.7	
22	17/0.16	8	0.23	1.30	11.4	
22	17/0.16	9	0.23	1.30	11.9	
22	17/0.16	10	0.23	1.30	12.4	
22	17/0.16	12	0.23	1.30	13.2	
22	17/0.16	14	0.23	1.30	13.5	
22	17/0.16	16	0.23	1.30	13.8	
22	17/0.16	18	0.23	1.30	14.7	
22	17/0.16	20	0.23	1.30	15.6	
22	17/0.16	25	0.23	1.30	18.0	
22	17/0.16	30	0.23	1.30	18.5	
22	17/0.16	40	0.23	1.30	20.5	
22	17/0.16	50	0.23	1.30	22.9	