



UL2464系列電纜

鋁箔隔離-單隔離

產品說明 Product manual

標準:UL2464

鋁箔麥拉遮蔽+地線

規格:18AWG-24AWG

芯數:2C-100C

導體:鍍錫銅

絕緣:SR-PVC

外被:PVC

耐溫:80°C

標準電壓:300V

線號	線數/線徑	芯數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Core	MM	MM	MM	Product
24	7/0.20	3	0.23	1.10	4.0	
24	7/0.20	4	0.23	1.10	4.5	
24	7/0.20	6	0.23	1.10	5.5	
24	7/0.20	7	0.23	1.10	5.5	
24	7/0.20	8	0.23	1.10	5.5	
24	7/0.20	9	0.23	1.10	6.0	
24	7/0.20	10	0.23	1.10	6.0	
24	7/0.20	12	0.23	1.10	6.4	
24	7/0.20	16	0.23	1.10	7.5	
24	7/0.20	20	0.23	1.10	7.8	
24	7/0.20	25	0.23	1.10	8.7	
24	7/0.20	37	0.23	1.10	10.0	
24	7/0.20	50	0.23	1.10	11.4	

線號	線數/線徑	芯數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Core	MM	MM	MM	Product
22	7/0.20	3	0.23	1.30	4.5	
22	7/0.20	4	0.23	1.30	5.0	
22	7/0.20	6	0.23	1.30	6.0	
22	7/0.20	7	0.23	1.30	6.0	
22	7/0.20	8	0.23	1.30	6.4	
22	17/0.16	9	0.23	1.30	6.5	
22	17/0.16	10	0.23	1.30	6.5	
22	17/0.16	12	0.23	1.30	7.1	
22	17/0.16	16	0.23	1.30	7.8	
22	17/0.16	20	0.23	1.30	8.5	
22	17/0.16	25	0.23	1.30	10.1	
22	17/0.16	37	0.23	1.30	11.0	
22	17/0.16	50	0.23	1.30	14.0	