



UL2464系列電纜

鋁箔隔離-單隔離(對型)

產品說明 Product manual

標準:UL2464

對絞集合鋁箔麥拉加地線總體隔離

規格:18AWG-24AWG

芯數:2C-100C

導體:鍍錫銅

絕緣:SR-PVC

外被:PVC

耐溫:80°C

標準電壓:300V

線號	線數/線徑	對數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Pair	MM	MM	MM	Product
24	7/0.20	1	0.23	1.10	4.0	
24	7/0.20	2	0.23	1.10	5.2	
24	7/0.20	3	0.23	1.10	6.0	
24	7/0.20	4	0.23	1.10	6.5	
24	7/0.20	5	0.23	1.10	7.0	
24	7/0.20	6	0.23	1.10	7.5	
24	7/0.20	7	0.23	1.10	8.0	
24	7/0.20	8	0.23	1.10	8.5	
24	7/0.20	10	0.23	1.10	9.3	
24	7/0.20	12	0.23	1.10	10.0	
24	7/0.20	14	0.23	1.10	10.7	
24	7/0.20	16	0.23	1.10	11.5	
24	7/0.20	18	0.23	1.10	12.0	
24	7/0.20	20	0.23	1.10	12.5	
24	7/0.20	25	0.23	1.10	13.7	
24	7/0.20	30	0.23	1.10	14.2	
24	7/0.20	40	0.23	1.10	15.8	
24	7/0.20	50	0.23	1.10	18.5	

線號	線數/線徑	對數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Pair	MM	MM	MM	Product
22	17/0.16	1	0.23	1.30	4.2	
22	17/0.16	2	0.23	1.30	6.0	
22	17/0.16	3	0.23	1.30	6.5	
22	17/0.16	4	0.23	1.30	7.0	
22	17/0.16	5	0.23	1.30	8.0	
22	17/0.16	6	0.23	1.30	8.5	
22	17/0.16	7	0.23	1.30	8.8	
22	17/0.16	8	0.23	1.30	10.0	
22	17/0.16	10	0.23	1.30	10.5	
22	17/0.16	12	0.23	1.30	11.2	
22	17/0.16	14	0.23	1.30	11.8	
22	17/0.16	16	0.23	1.30	12.4	
22	17/0.16	18	0.23	1.30	12.9	
22	17/0.16	20	0.23	1.30	13.5	
22	17/0.16	25	0.23	1.30	15.4	
22	17/0.16	30	0.23	1.30	16.2	
22	17/0.16	40	0.23	1.30	18.8	
22	17/0.16	50	0.23	1.30	21.5	