



# UL2464系列電纜

## 鋁箔銅網隔離-雙隔離

### 產品說明 Product manual

標準:UL2464

鋁箔麥拉加鍍錫銅網整體隔離加地線

規格:18AWG-24AWG

芯數:2C-100C

導體:鍍錫銅

絕緣:SR-PVC

外被:PVC

耐溫:80°C

標準電壓:300V

線號	線數/線徑	芯數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Core	MM	MM	MM	Product
24	7/0.20	2	0.25	1.10	4.5	
24	7/0.20	3	0.25	1.10	4.7	
24	7/0.20	4	0.25	1.10	5.0	
24	7/0.20	5	0.25	1.10	5.3	
24	7/0.20	6	0.25	1.10	5.6	
24	7/0.20	7	0.25	1.10	5.6	
24	7/0.20	8	0.25	1.10	5.9	
24	7/0.20	9	0.25	1.10	6.3	
24	7/0.20	10	0.25	1.10	6.9	
24	7/0.20	12	0.25	1.10	7.1	
24	7/0.20	15	0.25	1.10	7.5	
24	7/0.20	16	0.25	1.10	7.7	
24	7/0.20	20	0.25	1.10	8.5	
24	7/0.20	25	0.25	1.10	9.3	
24	7/0.20	30	0.25	1.10	10.0	
24	7/0.20	37	0.25	1.10	10.8	
24	7/0.20	40	0.25	1.10	11.1	
24	7/0.20	50	0.25	1.10	12.6	

線號	線數/線徑	芯數	絕緣厚度	芯線外徑	完成外徑	產品編號
AWG	NO/MM	Core	MM	MM	MM	Product
22	7/0.254	2	0.25	1.10	4.9	
22	7/0.254	3	0.25	1.10	5.1	
22	7/0.254	4	0.25	1.10	5.4	
22	7/0.254	5	0.25	1.10	5.8	
22	7/0.254	6	0.25	1.10	6.2	
22	7/0.254	7	0.25	1.10	6.2	
22	7/0.254	8	0.25	1.10	6.8	
22	7/0.254	9	0.25	1.10	7.2	
22	7/0.254	10	0.25	1.10	7.7	
22	7/0.254	12	0.25	1.10	7.9	
22	7/0.254	15	0.25	1.10	8.6	
22	7/0.254	16	0.25	1.10	8.8	
22	7/0.254	20	0.25	1.10	9.8	
22	7/0.254	25	0.25	1.10	10.9	
22	7/0.254	30	0.25	1.10	11.6	
22	7/0.254	37	0.25	1.10	12.4	
22	7/0.254	40	0.25	1.10	13.0	
22	7/0.254	50	0.25	1.10	14.4	