



鋁箔各隔+鋁箔銅網總隔規格書

UL2464 | CHENG HWA ENTERPRISE CO.,LTD.

產品簡介:

對絞集合每對鋁箔麥拉個別遮蔽加地線；再鋁箔麥拉鍍錫銅網整體隔離加地線

導體:鍍錫銅

絕緣:SR-PVC

外被材質:PVC

耐溫:80°C

標準電壓:300V

產品規格:

品名 AWG	線數/線徑 No/mm	對數 Pair	絕緣厚度 (mm)	芯線外徑 (mm)	完成外徑 (mm)
24	7/0.20	2	0.23	1.10	5.5
24	7/0.20	3	0.23	1.10	6.5
24	7/0.20	4	0.23	1.10	7.0
24	7/0.20	5	0.23	1.10	8.0
24	7/0.20	6	0.23	1.10	9.2
24	7/0.20	7	0.23	1.10	9.6
24	7/0.20	8	0.23	1.10	9.9
24	7/0.20	9	0.23	1.10	10.4
24	7/0.20	10	0.23	1.10	11.0
24	7/0.20	12	0.23	1.10	12.1
24	7/0.20	14	0.23	1.10	12.7
24	7/0.20	16	0.23	1.10	13.4
24	7/0.20	18	0.23	1.10	13.9
24	7/0.20	20	0.23	1.10	14.5
24	7/0.20	25	0.23	1.10	16.6
24	7/0.20	30	0.23	1.10	17.5
24	7/0.20	40	0.23	1.10	19.0
24	7/0.20	50	0.23	1.10	20.8

鄭華企業有限公司 | <http://www.cheng-hwa.com.tw>

桃園市桃園區鎮東街 5 號 | 03-3341764

22	17/0.16	2	0.23	1.30	6.0
22	17/0.16	3	0.23	1.30	7.0
22	17/0.16	4	0.23	1.30	7.5
22	17/0.16	5	0.23	1.30	8.7
22	17/0.16	6	0.23	1.30	10.0
22	17/0.16	7	0.23	1.30	10.7
22	17/0.16	8	0.23	1.30	11.4
22	17/0.16	9	0.23	1.30	11.9
22	17/0.16	10	0.23	1.30	12.4
22	17/0.16	12	0.23	1.30	13.2
22	17/0.16	14	0.23	1.30	13.5
22	17/0.16	16	0.23	1.30	13.8
22	17/0.16	18	0.23	1.30	14.7
22	17/0.16	20	0.23	1.30	15.6
22	17/0.16	25	0.23	1.30	18.0
22	17/0.16	30	0.23	1.30	18.5
22	17/0.16	40	0.23	1.30	20.5
22	17/0.16	50	0.23	1.30	22.9