



鋁箔銅網隔離-雙隔離(對型)規格書

UL2464 | CHENG HWA ENTERPRISE CO.,LTD.

產品簡介:

鋁箔麥拉加鍍錫銅網整體隔離加地線

導體:鍍錫銅

絕緣:SR-PVC

外被材質:PVC

耐溫:80°C

標準電壓:300V

產品規格:

| 品名 AWG | 線數/線徑 No/mm | 對數 Pair | 絕緣厚度 (mm) | 芯線外徑 (mm) | 完成外徑 (MM) |
|-----------|----------------|------------|--------------|--------------|--------------|
| 24 | 7/0.20 | 1 | 0.23 | 1.10 | 4.3 |
| 24 | 7/0.20 | 2 | 0.23 | 1.10 | 6.0 |
| 24 | 7/0.20 | 3 | 0.23 | 1.10 | 6.5 |
| 24 | 7/0.20 | 4 | 0.23 | 1.10 | 6.7 |
| 24 | 7/0.20 | 5 | 0.23 | 1.10 | 7.0 |
| 24 | 7/0.20 | 6 | 0.23 | 1.10 | 7.5 |
| 24 | 7/0.20 | 7 | 0.23 | 1.10 | 8.0 |
| 24 | 7/0.20 | 8 | 0.23 | 1.10 | 8.5 |
| 24 | 7/0.20 | 10 | 0.23 | 1.10 | 9.0 |
| 24 | 7/0.20 | 12 | 0.23 | 1.10 | 10.0 |
| 24 | 7/0.20 | 14 | 0.23 | 1.10 | 11.0 |
| 24 | 7/0.20 | 16 | 0.23 | 1.10 | 11.5 |
| 24 | 7/0.20 | 18 | 0.23 | 1.10 | 12.0 |
| 24 | 7/0.20 | 20 | 0.23 | 1.10 | 12.5 |
| 24 | 7/0.20 | 25 | 0.23 | 1.10 | 13.0 |
| 24 | 7/0.20 | 30 | 0.23 | 1.10 | 14.0 |
| 24 | 7/0.20 | 40 | 0.23 | 1.10 | 15.5 |
| 24 | 7/0.20 | 50 | 0.23 | 1.10 | 18.5 |

鄭華企業有限公司 | <http://www.cheng-hwa.com.tw>

桃園市桃園區鎮東街 5 號 | 03-3341764

| | | | | | |
|----|---------|----|------|------|------|
| 22 | 17/0.16 | 1 | 0.23 | 1.30 | 5.0 |
| 22 | 17/0.16 | 2 | 0.23 | 1.30 | 6.0 |
| 22 | 17/0.16 | 3 | 0.23 | 1.30 | 7.0 |
| 22 | 17/0.16 | 4 | 0.23 | 1.30 | 7.5 |
| 22 | 17/0.16 | 5 | 0.23 | 1.30 | 8.0 |
| 22 | 17/0.16 | 6 | 0.23 | 1.30 | 8.5 |
| 22 | 17/0.16 | 7 | 0.23 | 1.30 | 9.0 |
| 22 | 17/0.16 | 8 | 0.23 | 1.30 | 9.5 |
| 22 | 17/0.16 | 10 | 0.23 | 1.30 | 11.0 |
| 22 | 17/0.16 | 12 | 0.23 | 1.30 | 12.1 |
| 22 | 17/0.16 | 14 | 0.23 | 1.30 | 12.8 |
| 22 | 17/0.16 | 16 | 0.23 | 1.30 | 13.6 |
| 22 | 17/0.16 | 18 | 0.23 | 1.30 | 14.2 |
| 22 | 17/0.16 | 20 | 0.23 | 1.30 | 15.1 |
| 22 | 17/0.16 | 25 | 0.23 | 1.30 | 16.2 |
| 22 | 17/0.16 | 30 | 0.23 | 1.30 | 16.8 |
| 22 | 17/0.16 | 40 | 0.23 | 1.30 | 18.6 |
| 22 | 17/0.16 | 50 | 0.23 | 1.30 | 22.0 |