



鋁箔銅網隔離-雙隔離規格書

UL2464 | CHENG HWA ENTERPRISE CO.,LTD.

產品簡介:

鋁箔麥拉加鍍錫銅網整體隔離加地線

導體:鍍錫銅

絕緣:SR-PVC

外被材質:PVC

耐溫:80°C

標準電壓:300V

產品規格:

品名 AWG	線數/線徑 No/mm	芯數 Core	絕緣厚度 (mm)	芯線外徑 (mm)	完成外徑 (MM)
24	7/0.20	2	0.23	1.10	4.5
24	7/0.20	3	0.23	1.10	4.7
24	7/0.20	4	0.23	1.10	5.0
24	7/0.20	5	0.23	1.10	5.3
24	7/0.20	6	0.23	1.10	5.6
24	7/0.20	7	0.23	1.10	5.6
24	7/0.20	8	0.23	1.10	5.9
24	7/0.20	9	0.23	1.10	6.3
24	7/0.20	10	0.23	1.10	6.9
24	7/0.20	12	0.23	1.10	7.1
24	7/0.20	15	0.23	1.10	7.5
24	7/0.20	16	0.23	1.10	7.7
24	7/0.20	20	0.23	1.10	8.5
24	7/0.20	25	0.23	1.10	9.3
24	7/0.20	30	0.23	1.10	10.0
24	7/0.20	37	0.23	1.10	10.8
24	7/0.20	40	0.23	1.10	11.1
24	7/0.20	50	0.23	1.10	12.6

鄭華企業有限公司 | <http://www.cheng-hwa.com.tw>

桃園市桃園區鎮東街 5 號 | 03-3341764

22	17/0.16	2	0.23	1.30	4.9
22	17/0.16	3	0.23	1.30	5.1
22	17/0.16	4	0.23	1.30	5.4
22	17/0.16	5	0.23	1.30	5.8
22	17/0.16	6	0.23	1.30	6.2
22	17/0.16	7	0.23	1.30	6.2
22	17/0.16	8	0.23	1.30	6.8
22	17/0.16	9	0.23	1.30	7.2
22	17/0.16	10	0.23	1.30	7.7
22	17/0.16	12	0.23	1.30	7.9
22	17/0.16	15	0.23	1.30	8.6
22	17/0.16	16	0.23	1.30	8.8
22	17/0.16	20	0.23	1.30	9.8
22	17/0.16	25	0.23	1.30	10.9
22	17/0.16	30	0.23	1.30	11.6
22	17/0.16	37	0.23	1.30	12.4
22	17/0.16	40	0.23	1.30	13.0
22	17/0.16	50	0.23	1.30	14.4