



鋁箔隔離電腦電纜-對型

UL2464 ALUMINUM FOIL SHIELD COMPUTER CABLE | CHENG HWA ENTERPRISE CO.,LTD.

- 導體：鍍錫軟銅線絞合
- 芯線：SR-PVC 絕緣，二芯對絞
- 遮蔽：鋁箔麥拉+地線遮蔽
- 外被：80°C PVC
- 導體電阻最大：24AWG 86.0Ω/KM 以下(20 °C)
- 絕緣電阻最小：20Ω/KM 以上(20 °C)
- 耐電壓：300V
- 適用資料傳輸、科學儀器、RS-232 電腦系統等

線號 AWG	導體 條數/mm	對數 Pair	芯線外徑 m / m	完成外徑 m / m
24	7/0.20	2P	1.1	5.2
		3P	1.1	5.4
		4P	1.1	6.3
		5P	1.1	6.7
		6P	1.1	7.3
		7P	1.1	7.3
		8P	1.1	8.2
		10P	1.1	9.5
		12P	1.1	10.0
		16P	1.1	11.3
		20P	1.1	12.2
		24P	1.1	13.6
		30P	1.1	14.3
		36P	1.1	15.5
		50P	1.1	17.8
60P	1.1	19.5		

單層對型鋁箔麥拉整體隔離電腦信號電纜

The diagram illustrates the internal structure of the cable. It shows a central conductor surrounded by a layer of Aluminum/Malar (aluminum foil) for shielding. A Drain wire is also present, and the entire assembly is encased in a PVC jacket. The insulation for the individual conductors is SR-PVC.

鄭華企業有限公司 | <http://www.cheng-hwa.com.tw>

桃園市桃園區鎮東街 5 號 | 03-3341764

-導體：鍍錫軟銅線絞合

-芯線：SR-PVC 絕緣，二芯對絞

-遮蔽：鋁箔麥拉+地線遮蔽

-外被：80°C PVC

-導體電阻最大：22AWG 55.0Ω/KM 以下(20 °C)

-絕緣電阻最小：20Ω/KM 以上(20 °C)

-耐電壓：300V

-適用資料傳輸、科學儀器、RS-232 電腦系統等

線號 AWG	導體 條數/mm	對數 Pair	芯線外徑 m / m	完成外徑 m / m
22	7/0.254	2P	1.3	5.8
		3P	1.3	6.1
		4P	1.3	7.0
		5P	1.3	7.8
		6P	1.3	8.6
		7P	1.3	8.6
		8P	1.3	9.5
		10P	1.3	11.0
		12P	1.3	11.7
		16P	1.3	12.8
		20P	1.3	13.8
		24P	1.3	15.5
		30P	1.3	16.5
		36P	1.3	18.0
		50P	1.3	20.5
60P	1.3	22.5		

單層對型鋁箔麥拉整體隔離電腦信號電纜